



EUROSOL PETROL-SYSTEM

FOR USE IN ALL PETROL ENGINES TO IMPROVE FUEL QUALITY IN ACCORDANCE WITH DIN EN 228. ALSO SPECIALLY SUITED TO CATALYTIC CONVERTER AND TURBO SYSTEMS.

- ELIMINATES ALL CONTAMINATION WHICH BUILDS UP IN THE ENTIRE FUEL SYSTEM DURING SERVICE - FROM THE FUEL TANK TO THE COMBUSTION CHAMBERS
- REMOVES GUMMING AND AGGLUTINATION IN THE CARBURETTORS, FUEL DISTRIBUTORS AND INJECTOR NOZZLES
- REMOVES CARBURISED DEPOSITS AND SOOT BUILD-UP THROUGHOUT THE ENTIRE UPPER CYLINDER AREA
- REMOVES STEAM AND CONDENSATION FROM THE ENTIRE FUEL SYSTEM
- LUBRICATES AND PROTECTS THE UPPER CYLINDER AREA
- ELIMINATES UNPLEASANT AND UNHEALTHY SULPHUR ODOURS IN VEHICLES FITTED WITH CATALYTIC CONVERTERS

RESULTS:

- ✓ CLEAN, POWERFUL COMBUSTION
- ✓ NOTICEABLE FUEL SAVINGS
- ✓ PROTECTION AGAINST RUST AND CORROSION
- ✓ COMPLIANCE WITH SPECIFIED EXHAUST EMISSIONS LIMITS IN ACCORDANCE WITH PARAGRAPHS 47A AND 47B OF GERMANY'S VEHICLE REGISTRATION ACT
- ✓ FUNCTIONAL GUARANTEE FOR EXTENDED CATALYTIC CONVERTER SERVICE LIFE

APPLICATION:

EUROSOL PETROL-SYSTEM SHOULD BE ADDED TO THE FUEL TANK AT EACH SERVICE INTERVAL SPECIFIED BY THE MANUFACTURER.

400 ML ARE SUFFICIENT FOR 150 LITRES OF PETROL.

EUROSOL GUARANTEES THE HIGHEST PRODUCT QUALITY COMBINED WITH A STRICT POLICY OF TAKING ENVIRONMENTAL ISSUES INTO CONSIDERATION. EUROSOL PRODUCTS HAVE BEEN DEVELOPED TO MEET THE NEEDS OF TODAY'S MODERN TECHNOLOGY.